



Altra-Air *Sailfin*

QUOTATION SUBMITTAL

12 FT (3.7 M) FAN

Subject to Changes Without Notification.

ENVIRA-NORTH
SYSTEMS LIMITED

(519) 527-2198
enviranorth.com



3.7 M (12 FT) ALTRA-AIR SAILFIN FAN SPECIFICATIONS

General

Model Number.....	EN675X5006
Diameter.....	3.7 m (12 ft)
Number of Blades.....	5
Motor Power.....	0.75 kW (1 HP)
Noise Level.....	62.5 dBA
Weight (no mount).....	111 kgs (245 lbs)
Packaged Fan (30" x 31" x 32").....	128.8 kgs (284 lbs*)
Packaged Blades (11" x 11" x 72").....	50.4 kgs (111 lbs)

* Mounts, extensions & controls packages separately. Weights may vary.



Performance

Maximum Velocity.....	1.96 m/s (386 ft/min)
Airflow.....	33,236 l/s (70,424 CFM)
Maximum Speed.....	105 RPM
Power Usage.....	782 W
Maximum Effective Diameter.....	24 m (80 ft)

Construction

Frame.....	Galvanized Steel Frame
Hub.....	713 Cast Aluminum Alloy
Blades.....	6063 Extruded Anodized Aluminum
Blade End Caps.....	High Impact Polystyrene

Safety Components

Safety Cables.....	3/16" Stainless Steel
Guy Wires.....	1/8" Stainless Steel
Safety Clips.....	Zinc Plated Steel

Mounting Hardware

Standard Mount.....	Universal I-Beam Clamp w/ Swivel
Standard Drop.....	1 ft / 2 ft / 4 ft
Drop Extensions (Optional).....	1 ft / 2 ft / 4 ft

Mounting

Open Web Steel Joist (Optional).....	Steel Beam With Brackets
Wood Beam Mount (Optional).....	Steel Machined Mount Plates
Concrete Beam Mount (Optional).....	Steel Beam with Matching Mount Plates
Purlin "Z" Mount (Optional).....	Steel Beam Brackets
Steel Thickness Varies Depending on Beam Span.....	Consult Factory for Specifics

*Please see Altra-Air Installation Guide for more information regarding mounting hardware.

Gear Motor

Type.....	Helical Inline Reducer
HP.....	1 HP (50 Hz / 60 Hz)
Ratio.....	13.39
Volts.....	230 V / 400 V / 460 V / 575 V
Amps Consumed.....	3 A @ 230 V
Insulation Class.....	F
Torque.....	53 Nm (39 ft-lbs)
Thrust.....	125 N (28 lbs)

Fan Control

Enclosure.....	IP65
Operation.....	Key Pad
Control Options (Not Included).....	Low Voltage / Temperature Control
Standard Power.....	208 V / 230 V / 400 V / 460 V / 575 V
Special Wiring (Thermostats, Fire Alarm Interface, Networking Etc.)(Optional).....	Consult Factory
50 / 60 Hz Operation	

Warranty

Motor, Gearbox & Control Panel.....	3 Years
Blades, Hub & Mounting System.....	Lifetime

*Please see Altra-Air Installation Guide for warranty specifications and exclusions.

Tel: 1-519-527-2198 Fax: 1-519-527-2560
Toll Free: 1-886-771-7766

bigair@enviranorth.com

139 Sparling St. P.O Box 668
Seaforth, Ontario
Canada N0K 1W0

enviranorth.com

